



APPLICATION
TRACTOR



BIAS TRACTOR

FRONT TYRES

- Penetrates deep into soil for maximum steering control & minimal lateral side-slip because of its high center rib.
- Best for handling heavy loads on hard-packed surfaces.
- Offers excellent load distribution and flotation.



SIZE	PATTERN	PLY RATING	RIM WIDTH inch	TT or TL	SECTION WIDTH	OVERALL DIAMETER	STATIC LOADED RADIUS	ROLLING CIRCUM ± 2.5 %	NSD	LOAD CAPACITY	INFLATION PRESSURE	LOAD INDEX	SPEED								
													kmph	mph							
3.50-6	F-2	4	2.5	TT	99	3.9	343	13.5	214	8.4	1341	52.8	10	13	165	363	2.7	38	45	A8/40kmph	A8/25mph
3.50-8	F-2	4	2.5	TT	101	4.0	371	14.6	218	8.6	1390	54.7	9	11	185	407	2.7	38	49	A8/40kmph	A8/25mph
4.00-8	F-2	4	3.0	TT	112	4.4	430	16.9	224	8.8	1430	56.3	9	11	225	495	2.8	40	56	A8/40kmph	A8/25mph
4.00-12	F-2	4	3.0	TT	112	4.4	530	20.8	254	10.0	1626	64.0	10	13	300	660	2.8	27	66	A8/40kmph	A8/25mph
4.00-15	F-2	4	3.0	TT	112	4.4	610	24.0	295	11.6	1854	73.0	8	10	290	638	2.8	27	65	A8/40kmph	A8/25mph
5.00-15	F-2	6	4.0	TT	140	5.5	655	25.8	305	12.0	1956	77.0	12	15	475	1045	4.8	54	90	A8/40kmph	A8/25mph
	SW-201	4	3.0	TT	140	5.5	655	25.8	305	12.0	1956	77.0	14	18	475	1045	3.8	54	82	A8/40kmph	A8/25mph
4.00-16	SW-99	6	4.0	TT	140	5.5	655	25.8	305	12.0	1956	77.0	14	18	475	1045	3.8	54	82	A8/40kmph	A8/25mph
	F-2	4	3.0	TT	112	4.4	640	25.2	305	12.0	1956	77.0	10	13	325	715	3.5	50	69	A8/40kmph	A8/25mph
4.50-16	SW-201	8	3.0	TT	112	4.4	640	25.2	305	12.0	1956	77.0	10	13	325	715	3.5	50	69	A8/40kmph	A8/25mph
	F-2	6	3.0	TT	122	4.8	665	26.2	305	12.0	1956	77.0	10	13	365	803	3.3	47	73	A8/40kmph	A8/25mph
5.00-16	SW-201	6	3.0	TT	122	4.8	665	26.2	305	12.0	1956	77.0	10	13	365	803	3.3	47	73	A8/40kmph	A8/25mph
	F-2	6	4.0	TT	140	5.5	680	26.8	330	13.0	2032	80.0	10	13	400	880	4.2	60	76	A8/40 kmph	A8/25mph
5.50-16	SW-201	6	4.0	TT	140	5.5	680	26.8	330	13.0	2032	80.0	10	13	400	880	4.2	60	76	A8/40kmph	A8/25mph
	F-2	6	4.0	TT	150	5.9	710	27.9	330	13.0	2083	82.0	12	15	500	1100	3.7	54	84	A8/40kmph	A8/25mph
	SW-201	6	4.0	TT	150	5.9	710	27.9	330	13.0	2083	82.0	12	15	500	1100	3.7	54	84	A8/40kmph	A8/25mph
6.00-16	SW-99	6	4.0	TT	150	5.9	710	27.9	330	13.0	2083	82.0	12	15	500	1100	3.8	54	78	A8/40kmph	A8/25mph
	F-2	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
	SW-99	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
	SW-101	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
6.50-16	SW-201	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
	TF-2000	8	4.5	TT	165	6.5	745	29.3	356	14.0	2184	86.0	13	16	670	1474	4.6	65	94	A8/40kmph	A8/25mph
	F-2	8	4.5	TT	175	6.8	760	29.9	356	14.0	2286	90.0	13	16	750	1650	4.3	61	98	A8/40kmph	A8/25mph
	SW-101	8	4.5	TT	175	6.8	760	29.9	356	14.0	2286	90.0	13	16	750	1650	4.3	61	98	A8/40kmph	A8/25mph
7.50-16	SW-201	8	4.5	TT	175	6.8	760	29.9	356	14.0	2286	90.0	13	16	750	1650	4.3	61	98	A8/40kmph	A8/25mph
	F-2	8	5.5	TT	205	8.0	808	31.8	381	15.0	2413	95.0	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph
	SW-101	8	5.5	TT	205	8.0	808	31.8	381	15.0	2413	95.0	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph
	SW-201	8	5.5	TT	205	8.0	808	31.8	381	15.0	2413	95.0	14	18	875	1925	3.8	54	103	A8/40kmph	A8/25mph
9.00-16	SW-201	12	5.5	TT	205	8.0	808	31.8	381	15.0	2413	95.0	14	18	1350	2970	4.0	57	119	A8/40kmph	A8/25mph
	F-2	10	7.0	TT/TL	234	9.2	854	33.6	406	16.0	2540	100.0	15	19	1250	2750	3.9	55	116	A8/40kmph	A8/25mph
	F-2	10	7.0	TT/TL	275	10.8	900	35.4	406	16.0	2692	106.0	18	23	1360	2992	2.9	41	119	A8/40kmph	A8/25mph
11.00-16	F-2	12	10	TT/TL	320	12.6	970	38.1	457	18.0	2896	114.0	23	29	1600	3520	2.5	48	124	A8/40kmph	A8/25mph
6.00-18	SW-201	8	4.5	TT	165	6.5	795	31.3	457	18.0	2340	92.1	11	14	710	1562	3.3	47	96	A8/40kmph	A8/25mph
7.50-18	F-2	8	5.5	TT	204	8.0	867	34.2	406	16.0	2565	101.0	14	18	950	2090	3.8	54	106	A8/40kmph	A8/25mph



APPLICATION
TRACTOR



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
7.50-18	SW-101	8	5.5	TT	203	8.0	869	34.2	406	16.0	2565	101.0	14	18	950	2090	3.8	54	106	A8/40 kmph	A8/25mph
	SW-201	8	5.5	TT	203	8.0	869	34.2	406	16.0	2565	101.0	14	18	950	2090	3.8	54	106	A8/40 kmph	A8/25mph
4.00-19	F-2	6	3.0	TT	112	4.4	712	28.0	330	13.0	2134	84.0	10	13	355	781	3.4	48	72	A8/40 kmph	A8/25mph
6.00-19	F-2	8	4.5	TT	165	6.5	814	32.0	381	15.0	2413	95.0	12	15	925	2035	4.2	60	105	A8/40 kmph	A8/25mph
	SW-201	8	4.5	TT	165	6.5	814	32.0	381	15.0	2413	95.0	12	15	925	2035	4.2	60	105	A8/40 kmph	A8/25mph
6.50-20	F-2	8	4.5	TT	173	6.8	864	34.0	406	16.0	2565	101.0	15	19	850	1870	4.6	65	102	A8/40 kmph	A8/25mph
	SW-201	8	4.5	TT	173	6.8	864	34.0	406	16.0	2565	101.0	15	19	850	1870	4.6	65	102	A8/40 kmph	A8/25mph
	SW-200	8	4.5	TT	173	6.8	864	34.0	406	16.0	2565	101.0	16	20	850	1870	4.6	65	102	A8/40 kmph	A8/25mph
7.50-20	SW-99	8	5.5	TT	203	8.0	920	36.2	432	17.0	2718	107.0	16	20	1030	2266	3.5	50	109	A8/40 kmph	A8/25mph
	F-2	8	5.5	TT	203	8.0	920	36.2	432	17.0	2718	107.0	16	20	1030	2266	3.5	50	109	A8/40 kmph	A8/25mph
	SW-201	8	5.5	TT	203	8.0	920	36.2	432	17.0	2718	107.0	16	20	1030	2266	3.5	50	109	A8/40 kmph	A8/25mph
	DUAL RIB PLANTER	8	5.5	TT	203	8.0	942	37.1	442	17.4	2718	107.0	19	24	1030	2266	3.5	50	109	A8/40 kmph	A8/25mph