

Reusable Full-Face Shield Specification Sheet

**Clear Shield – CRYSTAL VINYL 500 (Size – 300mm x 300mm Radius Base)
0.5MM Heavy Duty Vinyl**

Width	0,75cm - 250cm 29,5 – 98,5 inch	Testing Method
Solar Transmission	90%	
Optional Super Clear	AVAILABLE	
Thickness	0,50mm	
Total Weight	610g/m ² 18 OZ/YD2	DIN EN ISO 2286-2 BS 3424 Method 5A
Composition	PVC	DIN EN ISO 2286-2 BS 3424 Method 5B
Surface Type	GLOSSY	
Lacquering (optional)	L 1/1	
Breaking strength Warp	400 N/5cm 90 LBS/2inch	DIN 53 354 BS 3424 Method 6A FS5100
Breaking Strength Weft	400 N/5cm 90 LBS/2ich	DIN 53 354 BS 3424 Method 6A FS5100
Tear Strength Warp	110 N 25LBS	DIN 53 363 BS 3424 Method FS 5134
Tear Strength Weft	110 N 25 LBS	DIN 53 363 BS 3424 Method FS 5134
Weldbilty	Hi Frequency/ Hot Air	
Temperature resistance	-30'C/+70'C	DIN EN 1876-2 BS 3424 Method 10 FS 5874
Light Fastness	Grade 7 and above	DIN EN ISO 877 BS 3424 Method 15
Flammability (optional)	M1, M2 B1, B2 PASS Small, Large Scale	NFP 92.503 DIN 4102 DIN 75200 NFPA-701
Packing	Roll OR CTNS	
All our technical characteristics are indicative		

Head Strap - Carrier Tape (Length – 660mm)

Width	30mm
Colour	Black
Material	100% Polypropylene
Fastening	Velcro