

# EV6500

## Hand-Held Dual-Light LED UV Lamp

The EV6500 is a hand-held, portable LED UV lamp with built-in white light LEDs for non-destructive testing applications like fluorescent penetrant testing and fluorescent magnetic particle inspections.

Designed with broad-beam profile for in-line and hand-held use, the EV6500 will decrease inspection time by improving indication visibility with 7,000  $\mu\text{W}/\text{cm}^2$  high intensity UV-A illumination and the widest coverage area in its class.

To improve NDT inspection flexibility, the EV6500 has easy-on white light LEDs for visible flaw location, eliminating the need for a separate flashlight. The white light LEDs provide a large, concentrated flood of visible light of over 150 ft-candles.



### BENEFITS

#### Minimizes time to inspect parts with wide, intense UV beam

- Speeds up inspection time with the widest, most even beam on the market
- Indications are clearly visible even at the edge of the 10 inch / 25 cm beam, thanks to the high intensity LEDs

#### Improves visibility & versatility with built-in white light LEDs

- Eliminates the need for a separate flashlight for visible spot checking with built-in LED white light function
- See clearly without fumbling in the dark or having to turn on an overhead light with the 16 inch / 41 cm beam of bright white light

#### Increases real-world reliability with NDT-focused engineering and dependable construction

- Reduces on-the-job downtime with dependable, reinforced construction
- Fully sealed housing will stand up to the elements, along with a fan-less cooling system and non-clouding lens for reliable, consistent inspections
- Fully sealed IP65 rated housing will stand up to the elements

#### Safer working conditions with LED technology

- Removes the possibility of operator burns through cool LED technology
- Eliminates hazardous mercury vapor waste disposal for safer working conditions

## PRODUCT PROPERTIES

<b>Light Sources</b>	5 UV LEDs 4 White LEDs
<b>Light Filter</b>	Clear filter
<b>Peak Wavelength</b>	365 ±5 nm
<b>Max UV Intensity*</b>	7,000 μW/cm <sup>2</sup>
<b>UV Light Coverage*</b>	10 in / 25 cm diameter circular spot
<b>Visible Light in UV Mode</b>	< 1 ft-candle / 10 lux
<b>Visible Light in Visible Mode</b>	150 ft-candles / 1,600 lux
<b>Visible Light Coverage*</b>	16 in / 41 cm diameter circular spot
<b>Working Distance</b>	< 5 in / 13 cm
<b>Stabilization Time†</b>	5 minutes
<b>Lamp Cord Length</b>	17 ft / 5.18 m
<b>Power Supply Cord Length</b>	9 ft / 2.75 m
<b>Weight, Lamp</b>	2.8 lb / 1.3 kg
<b>Weight, Power Supply</b>	1.4 lb / 0.6 kg
<b>Power In</b>	100-240 VAC / 50-60 Hz / < 1 A

\* At 15 in / 38 cm

† At ambient conditions

## USE RECOMMENDATIONS

<b>NDT Method</b>	Fluorescent Penetrant Testing and Fluorescent Magnetic Particle Inspection
<b>Recommended Accessories</b>	UV-A Meter, PN 625024 Visible Light Meter, PN 622338 UV-A Safety Glasses, PN 506249

## FEATURES

- 10 in / 25 cm wide, uniform beam
- No hot-spots in the beam profile
- Built-in LED white light
- Single push-button operation for UV and white light
- Rugged, durable design
- No internal fan
- Low energy consumption
- Improved operator and environmental safety

## SPECIFICATION COMPLIANCE

- API 6A
- API 1104
- ASME BPVC
- ASTM E165
- ASTM E709
- ASTM F601
- AWS D1.1
- ISO 9934

## PART NUMBERS

Series	Model	What's Different?	Part Number
EV6500	North America	North American Type B Electrical Plug	626803
	Europe	European Type F Electrical Plug	629677