

1. IDENTIFICATION OF THE PREPARATION AND COMPANY
SAFETY DATA SHEET

White Grease

Issue No: AE04/03

Date: 17/07/03

Page 1 of 2

W.R.DAY LTD.
6 MANOR INDUSTRIAL ESTATE

COMEYTRWE
TAUNTON TA4 1EF

TEL. +44(0)1823 276506/7

FAX +44(0)1823 336336

INTERNET : www.autoday.com

2. COMPOSITIONAL INFORMATION

HAZARDOUS INGREDIENTS:

Low boiling point modified naphtha – naphtha (petroleum) solvent refined light

CAS: 64741-84-0 EINECS: 265-086-6 In neat form: F(R11); Xi (R38); N (R51/53); R67 10-30%

3. HAZARDS IDENTIFICATION

MAIN HAZARDS : Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environment. Vapours may cause drowsiness and dizziness.

OTHER HAZARDS : In use may form flammable/explosive vapour-air mixture.

4. FIRST AID MEASURES

SYMPTOMS:

SKIN: May be irritation and redness at point of contact.

EYES: May be irritation and redness. Corneal burns may occur.

INGESTION: Possible nausea and stomach pain. May be vomiting. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation..

INHALATION: May be nausea and stomach pain. Vomiting may occur. May be drowsiness or mental confusion. May be loss of consciousness.

ACTION:

SKIN : Remove contaminated clothing and wash with clean water. Seek medical aid if symptoms persist.

EYES : Flush with water for 15 minutes. Seek medical aid.

INGESTION : Do not induce vomiting. Give water to drink. Seek immediate medical advice.

INHALATION : Remove casualty from exposure. If unconscious check breathing and apply artificial respiration if necessary. If breathing OK place in the recovery position. If conscious ensure casualty is lying down. If breathing becomes bubbly have casualty sit and provide oxygen if available. Summon immediate medical aid.

5. FIRE FIGHTING MEASURES

EXPOSURE HAZARDS : Extremely flammable. In combustion emits toxic fumes. Vapour may travel to source of ignition and flash back. Forms explosive air-vapour mixture.

EXTINGUISHING AGENTS : Carbon dioxide.

PRECAUTIONS : Wear self-contained breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition. Do not allow entry into rivers/drains. Absorb with inert absorbent.

7. HANDLING AND STORAGE

Store in cool well-ventilated area.

Keep away from sources of ignition. No smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: Ensure adequate ventilation.

Personal Protection:

If skin splashes are likely use gloves or barrier cream.

Wear suitable protective eye goggles.

Do not ingest.

Ensure adequate ventilation when using product.

Refer to Section 2 and HSE Guidance Note EH40 to establish current OEL / MEL values.

White Grease

Issue No : AE04/03

Date : 17/07/03

Page 2 of 2

9. PHYSICAL & CHEMICAL PROPERTIES

State : Aerosol
 Colour : White
 Odour : Characteristic
 Evaporation rate : Fast
 Oxidising : Non-oxidising (by EC criteria)
 Flash Point : -35DegC
 Solubility in water : Insoluble

10. STABILITY AND REACTIVITY

Product is stable under normal conditions. Avoid flames and sources of ignition. Avoid oxidising agents. In combustion emits toxic fumes of carbon dioxide and carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Ingredient : LOW BOILING POINT MODIFIED NAPHTHA – NAPHTHA (PETROLEUM) SOLVENT REFINED LIGHT

12. ECOLOGICAL INFORMATION

Mobility : Insoluble in water Absorbed only slowly into soil.
 Persistence and degradability : No data available
 No bioaccumulation data available.
 Other hazards : Toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID	UN No : 1950	ADR Class: 2
	Labelling 2.1	Shipping Name : Aerosols
IMDG/IMO	UN No 1950	Class: 2
	EmS: 2-13	Labelling: 2.1
IATA/ICAO	UN No : 1950	Class: 2
	Labelling : 2.1	

15. REGULATORY INFORMATION

SYMBOLS: EXTREMELY FLAMMABLE, IRRITANT, DANGEROUS FOR THE ENVIRONMENT
 RISK PHRASES :

R12 : Extremely flammable

R38 : Irritating to skin

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environment.

R67 : Vapours may cause drowsiness and dizziness.

SAFETY PHRASES :

S16 : Keep away from sources of ignition – No Smoking

S23 : Do not breathe aerosol.

S36/37: Wear suitable protective clothing and gloves.

S51 : Use only in well-ventilated areas.

PRECAUTIONARY: Pressurised container: protect from sunlight and do not expose to temps.

exceeding 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Keep out of the reach of children.

16. OTHER INFORMATION

Refer to product label for detailed instructions for use. The information in this Data Sheet is to be used in conjunction with the information on the product label. It is the responsibility of employers to ensure that all persons using or handling this product have access to and are aware of the information contained herein. Possession of this Data Sheet does not in itself constitute compliance with the HSAW Act or COSHH Regulations. Information herein is believed to be correct but does not purport to be all inclusive and should be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with this product.