

## 1.IDENTIFICATION OF THE PREPARATION AND COMPANY

### SAFETY DATA SHEET

# **Satin Black**

Issue No : AE12/02      Date : 27/11/02  
Page 1 of 2

## **W.R.DAY LTD**

6 MANOR INDUSTRIAL ESTATE  
COMEYTROWE  
TAUNTON TA4 1EF

TEL.+44(0)1823 276506 / 7  
FAX +44(0)1823 336336  
INTERNET : www.autoday.com

## 2.COMPOSITIONAL INFORMATION

Ingredients: Acetone 30-50%  
CAS 67-64-1                      EINECS: 200-662-2  
(F) R11, (Xi) R36, (Xi) R66, (-) R67

Black Paint 30-50%  
(-) R10, (Xn) R20, (Xi) R38

## 3.HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Harmful by inhalation. Irritating to eyes, skin and respiratory system.  
Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable/explosive vapour-air mixture.

## 4.FIRST AID MEASURES

SKIN : Remove contaminated clothing unless stuck to skin. Drench affected skin with running water for 10 minutes or longer if substance still on skin.  
Transfer to hospital if there are burns or symptoms of poisoning.  
EYES : Flush with water for 15 minutes and seek medical aid.  
INGESTION: Do not induce vomiting. Give water to drink. If unconscious check for breathing and apply artificial respiration if necessary.  
If unconscious and breathing is OK place in recovery position. Transfer to hospital.  
INHALATION : Remove casualty from exposure. If unconscious check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK place in the recovery position. If conscious ensure casualty sits or lies down.  
If breathing becomes bubbly, have casualty sit and provide oxygen if available.  
Transfer to hospital as soon as possible.

## 5.FIRE FIGHTING MEASURES

EXTINGUISHING AGENTS : Carbon dioxide, alcohol or polymer foam. Dry chemical powder.

EXPOSURE HAZARDS : Extremely flammable. In combustion emits toxic fumes.  
Vapour may travel considerable distance to source of ignition and flash back.  
Forms explosive vapour-air mixture.

PROTECTIVE MEASURES: Wear self-contained breathing apparatus.

## 6.ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Eliminate sources of ignition. Mark contaminated area with signs and prevent access to unauthorised personnel.  
ENVIRONMENTAL PRECAUTIONS: Prevent discharge into drains or rivers. Contain spillage using bunding.  
CLEAN-UP: Absorb into dry earth or sand. Wash the spillage site with water.

## 7.HANDLING AND STORAGE

HANDLING REQUIREMENTS: Ensure adequate ventilation. No smoking. Use non-sparking tools.

STORAGE CONDITIONS: Store in cool well-ventilated area. Keep away from sources of ignition.

**W.R.DAY LTD**

**SAFETY DATA SHEET**

Issue No : AE12/02

**Satin Black**

Date : 27/11/02

Page 2 of 2

### **8.EXPOSURE CONTROL / PERSONAL PROTECTION**

Ensure adequate ventilation when using product.  
Ensure lighting and electrical equipment are not ignition sources.  
Wear protective gloves and goggles. Wear appropriate clothing to prevent skin contact.  
Refer to HSE Guidance Note EH40 for current OEL/MEL values for hazardous ingredients.

### **9.PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Black aerosol paint  
Odour : Characteristic  
Solubility : Insoluble in water  
Flash Point : -26 DegC

### **10.STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.  
CONDITIONS TO AVOID: Sources of ignition.  
MATERIALS TO AVOID: Oxidising agents.

### **11.TOXICOLOGICAL INFORMATION**

ORAL LD50 : 5800mg/kg (Species Oral, Rat - calculated.)  
Skin contact may cause irritation.  
Eye contact may cause irritation and redness. Corneal burns may occur.  
Ingestion may cause stomach pain and vomiting. There may be loss of consciousness. Convulsions may occur.  
Inhalation may cause coughing or wheezing. There may be lung congestion causing shortness of breath. There may be loss of consciousness. Convulsions may occur.

### **12.ECOLOGICAL INFORMATION**

Mobility : Insoluble in water.

### **13.DISPOSAL CONSIDERATIONS**

Dispose of via a licensed waste disposal operator and in accordance with national and local authority regulations.

### **14. TRANSPORT INFORMATION**

ADR/RID	UN No 1950	ADR Class 2
	Labelling 2.1	Shipping Name : Aerosols.

### **15. REGULATORY INFORMATION**

SYMBOLS : EXTREMELY FLAMMABLE. HARMFUL  
RISK PHRASES : R12 Extremely flammable R20/21 Harmful by inhalation and in contact with skin.  
R36/38: Irritating to eyes and skin.  
R66: Repeated exposure may cause skin dryness or cracking.  
SAFETY PHRASES: S16 Keep away from sources of ignition. No smoking.  
S23 Do not breathe aerosol.  
S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice.  
S36/37 Wear suitable protective clothing and gloves.  
S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)  
S51 Use only in well ventilated areas.  
PRECAUTIONARY PHRASES: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 DegC.  
Do not pierce or burn even after use.  
Do not spray on naked flame or any incandescent material.  
Keep out of reach of children.

### **16.OTHER INFORMATION**

Refer to product label for detailed instructions for use. Information in this Data Sheet is to be used in conjunction with information on the product label. It is the responsibility of the employer to ensure that all persons using or handling this product have access to and are aware of the information contained herein. Possession of this Data Sheet does not in itself constitute compliance with the HSAW Act or COSHH Regulations.