

Technical Document
WEBNET Cat 6A 23awg 4pair
U/UTP LSNH Blue

webro

Part Number: 120551C-LSNH-BLU

Description: WEBNET Cat 6A U/UTP 23awg 4pair
Low Smoke Non-Halogen (LSNH) Blue



Product Construction

Conductor Material	:	Bare Copper
Conductor Size	:	Solid, 23(1)awg
Insulation Material	:	High Density Polyethylene (HDPE)
Number of Pairs	:	4
Pair Colours	:	Blue, Blue/White; Orange, Orange/White, Green, Green/White; Brown, Brown/White
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Blue



Mechanical Characteristics

Overall Diameter	:	6.2mm ± 0.20mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +50°C
Bend Radius	Fixed	4 x Overall Diameter
	Flexing	8 x Overall Diameter
Weight	:	50 kg/km

Electrical Characteristics

Max. Conductor DC Resistance	:	≤ 9.5 Ω/km @ 20°C
Max. Resistance Unbalanced	:	< 2%
Max. Insulation Resistance	:	> 5000 MΩ x m
Mutual Capacitance	:	< 60 pF/m
Capacitance Unbalanced	:	1600 pF/km
Impedance @ 100 MHz	:	100 Ω ± 5
Velocity of Propagation	:	66 %
Delay Skew	:	< 45 ns / 100m
Voltage Rating	:	125V

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	PS - NEXT (dB)	ACR (dB)	PS - ACR (dB)	ACRF (dB)	PS-ACRF (dB)	Return Loss (dB)
1	≤ 2.0	≥ 95	≥ 92	≥ 90	≥ 87	≥ 100	≥ 97	25
4	≤ 3.6	≥ 95	≥ 92	≥ 90	≥ 87	≥ 100	≥ 97	25
10	≤ 5.4	≥ 95	≥ 92	≥ 85	≥ 82	≥ 90	≥ 87	28
100	≤ 18.3	≥ 87	≥ 84	≥ 75	≥ 72	≥ 75	≥ 72	25
200	≤ 25.0	≥ 87	≥ 84	≥ 75	≥ 72	≥ 70	≥ 67	25
250	≤ 29.1	≥ 85	≥ 82	≥ 52	≥ 49	≥ 65	≥ 62	23
400	≤ 37.4	≥ 75	≥ 72	≥ 41	≥ 48	≥ 55	≥ 52	23
500	≤ 41.5	≥ 75	≥ 72	≥ 30	≥ 27	≥ 55	≥ 52	21

Performance @ 20°C

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2	Certification	:	HDBaseT 3.0
Low Smoke	:	BS EN 61034-2	RoHS 3 Compliant	:	Yes
Halogen Gas	:	BS EN 60754-1&2	REACH Compliant	:	Yes
Manufactured in Accordance to	:	TIA/EIA 568-C.2, IEC 11801 Class Ea, EN 50288-4-1, ISO/IEC 61156-5, EN 50173-1			
CE CPR Classification	:	Cca s1a, d1, a1 to EN 50575:2014+A1:2016			

CEDIA[®]
MEMBER



Publication Date: 07/06/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

Webro Cables & Connectors Ltd

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK
Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | www.webro.com

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.