


ORAPI



HIGH TECHNOLOGY CONSUMABLES FOR FOOD INDUSTRIES

REFERENCED PRODUCTS NSF





NEW !

BLUE CAPS ON AEROSOLS : MORE FOOD SAFETY

STANDARDS AND COMPLIANCE OF OUR PRODUCTS

Understanding your problems, anticipating your needs and responding to the standards of your industry...
ORAPI is committed to you in proposing products that meet standards for "unintentional contact with foodstuffs".

ORAPI products are :

- compliant with the FDA 21 CFR lists and the positive French list (Order of 8 September 1999)
- Kosher compliant
- Halal compliant
- compliant with the positive reference lists for contact with potable water (as part of a health compliance declaration) **ACS**
- recorded by the NSF :
 - H1 for lubricants – usable for unintentional contact with foodstuffs
 - 3H for lubricants - authorised for direct contact with foodstuffs
 - A1, C1 and D1 for detergents – cleaning in food-processing areas followed by rinsing with potable water - unintentional contact with foodstuffs
 - K1, K3, K6 for solvents - cleaning, degreasing food-processing equipment in non-food processing areas - followed by washing with a permitted detergent and rinsing with potable water
 - P1 and S6 for glues - use in food-processing areas



The NSF mark found on the Non-food Components indicates to food-safety inspectors and consumers that the product used in and around foodstuffs complies with food safety requirements.

www.nsfwhitebook.org

SOMMAIRE

P. 3

PENETRATE
& RELEASE

P. 3-5

CLEAN

P. 5-9

LUBRICATE

P. 9

CALFLUID

P. 10

FOUNTAINS

P. 11

ASSEMBLE

P. 12-13

TRANSNET

PENETRATE & RELEASE

REDUCE AL

FOOD INDUSTRIES

Low surface tension fluid. Infiltrates, penetrates, cleans, lubricates with a de-seizing effect. Preventive and curative action against rust. For all kind of seized mechanism, small tools, conditioner, fastenings, plumbing, manufacturing and packing of food...

799

Odour: none
Class : H1 (vrac)
H1 H2 (aero)



4799A2	405 ml aerosol TDS
2799J1	5 l jerrycan

DEGRYP'BIO®

BIODEGRADABLE, VOC-FREE

For difficult dismantling operations in places where environmental protection is key: forests, rivers, lakes, seas, gardens, etc. Formulated for minimal environmental impact, from plant-based lubricating, degreasing and tar removing raw materials. Fast acting. Wetting, penetrating, water repellent, rust and corrosion inhibitor.

817



Flash point:
> 150°C
Class : H1



4817A4	650 ml aerosol TDS
2817J1	5 l jerrycan
2817U2	200 l drum

SOLVENTS

ORASOLV A

VERY QUICK DRYING

Dry solvent. Penetrates deeply and completely dissolves greasy residues and glues. Does not cause metal oxidation once dry. Soluble in water. Can be used for the cleaning of glue residues, adhesives, labels, blood or sugar in a food processing environment.

568

colourless
Flash point:
< 21°C
Class : K1



4568A4	650 ml aerosol TDS
2568J1	5 l jerrycan
2568U2	200 l drum

ORASOLV N

MULTI-PURPOSE, ODOURLESS

Degreases mechanical parts. Cleans electrical and electronic components. Evaporates rapidly when blown dry. A3 type safety solvent..

513

colourless
odourless
Flash point:
> 60°C
Can be used in
ultrasonic cleaning
baths
strength Dielectric
:
> 40 kV
Class : K1



2513i2	1 l container
251301	20 l drum
2513U2	200 l drum



ORASOLV VEG 3 AL

SOLVENT 100% VEGETAL

Solvent formulated from very high-quality vegetable raw materials for efficient degreasing. NSF Approved for used in food industries

513V

NEW

colourless
Flash point : 66°C
IKB : 70
Class : K1



2513VJ1	5 l metal jerrycan
2513V01	20 l metal drum
2513VU2	200 l drum

ORASOLV T

RAPID EVAPORATION

For the cleaning of mechanical parts and stainless steel equipment. Excellent compatibility with gaskets, rubber and all plastics. Cleaning of food and pharmaceutical facilities.

544

colourless
Flash point:
< 40°C
Can be used in
fountain
Dielectric
strength:
> 40 kV
Class : A7, K1



2544i2	1 l container
2544J1	5 l jerrycan
254402	30 l metal drum
254405	60 l metal drum
2544U2	200 l drum

ORASOLV R2

VOC FREE

Penetrates deeply and completely dissolves greasy deposits. Leaves a light, greasy film which protects metals. Ideal solvent for safe cleaning, protects operators and the environment.

576

colourless
Transparent
liquid
Flash point :
> 100°C
Can be used in
ultrasonic cleaning
baths
strength Dielectric :
> 40 kV
Class : H1, K1



2576U2	200 l drum
--------	------------

NATUR'SOLV

PLANT-BASED SOLVENT

High-tech new generation solvent, synthesised from plant-based raw materials. Excellent degreaser and tar remover. Penetrates deeply and dissolves greasy deposits and dirty oils. Protects against corrosion, VOC-free.

582



colourless
odourless
Flash point :
> 150°C
Can be used in
ultrasonic cleaning
baths
strength Dielectric
:
> 40 kV
Class : K1, K2



2582J1	5 l jerrycan
2582U2	200 l drum

SOLVENTS

ORASOLV S1

543

INKS AND RESINS

High-tech solvent. Soluble in water; allows easy rinsing of surfaces. Used neat for the cleaning and degreasing of numerous chemicals: printing inks, resins and glues. Very efficient solvent.

■ Green
Flash point :
> 75°C
Can be used in
fountain
Dielectric strength:
> 40 kV
IKB : > 150
Class : K1, K3

2543i2	1 l container
2543J1	5 l jerrycan
2543O1	20 l drum
2543O5	60 l drum
2543U2	200 l drum
2543N1	Container 1000 l



DECOLETIK

5164

LABEL PULLER

High tech, fast evaporating solvent for fast and efficient label removal.

colorless
Class : K3



45164A4	650 ml aerosol
---------	----------------

DETERGENTS

ORANET F

536

DEGREASING CLEANER FOR BIOLOGICAL FOUNTAIN

Aqueous degreaser for all metal mechanical parts to be degreased with parts washer. To use with ORAZYM microorganisms 5327.

colourless
Dosage : pure
Class : A1



2536O1	20 l drum
--------	-----------

DELICAL

C027

FOOD EQUIPMENT DESCALER

Liquid descaler for water circuit and various materials, for food and agro-food industries (drinks dispenser, dishwasher...). Formula without hydrochloric acid, with a colour indicator to validate the operation efficiency.

■ yellow
pH : 1
Class : A3, C1



C027/0001	1 l can
C027/0005	5 l can
C027/0030	30 l drum

ORARENOV

535

ALUMINIUM STAINLESS STEEL RESTORER/STRIPPER

Removes greasy deposits and surface oxidation from metallic parts. Ideal for aluminium and stainless steel cleaning and maintenance. Excellent stripping compound. Ready to use. Can be used diluted.

colourless
pH : <1
Class : A8, C1



2535i2	1 kg container
2535J1	5 kg jerrycan
2535U2	200 kg drum

ORANET A

530

FOOD INDUSTRIES

Cleaning of tanks, truck tarpaulins, floors, machine frames, production and packaging of wine, beer, vegetables, meat, biscuits, dairy products etc. Can be used with a brush, in an automatic washing system, scrubber-drier or pressure washer.

colourless
odourless
Dosage :
0,5 to 20 %
Class : A1, A8



2530i2	1 kg container
2530J1	5 kg jerrycan
2530O1	20 kg drum
2530O5	60 kg drum
2530U2	200 kg drum

MECAMATIC

9062

SUPER ALKALINE LIQUID DETERGENT

Cleaning and renovation of very greasy and dirty surfaces. Floor cleaning in petrol stations, garages, stills, distillers in the food processing industry. Reserved for professional use. Used neat or diluted. Recommended for use in washing machines.

■ light brown
Liquid
pH : 13-14
Dosage : 10 %
Class : A1



29062J1	5 l jerrycan
29062O1	20 l drum
29062O5	60 l drum

NET MOUSS

5002

CLEANING FOAM

Cleaning foam for every supports. Computers, TV, laminated piece of furniture, luminous signs, plastic or metallic bumpers, photocopiers... Designed for heavily soiled surfaces, metallic or PVC construction.

■ white foam
Class : A1



45002A4	650 ml aerosol
---------	----------------

DETERGENTS

OURAGAN

5152

ALL IN ONE

Ready-to-use, multi-purpose disinfecting and deodorising detergent. Cleans and degreases all surfaces. For use in offices, workshops, changing rooms, kitchens, etc. Compliant with the EN 1040 and EN 1276 standards - bactericidal after 5 minutes - and the EN 1275 and EN 1650 standards - fungicidal in 15 minutes.



■ yellow green
Clear liquid
Scent:
menthol
eucalyptus
pH : 13,4
Class : D1



25152i1 500 ml spray bottle

ORANET S+

533

NON FOAMING

Very powerful multi-purpose cleaner for scrubber-driers and high-speed or ultrasonic cleaning equipment. Does not foam, even under heavy agitation. Biodegradable. Used for difficult factory cleaning operations: floors, tiles, changing rooms etc.

■ orange-yellow
Dosage :
2 to 15 %
8 % MAL
pH : 10,5
Class : C1



2533i2 1 l container

253301 20 l drum

2533U2 200 l drum

BRILLINOX

586

STAINLESS STEEL POLISHER AND RESTORER

Removes greasy films and stains while giving a lasting shine to cleaned surfaces: stainless steel, chrome etc. Polishing and protective properties. Dairies, breweries, machine frames, stainless steel structures, etc. Apply a small amount of product onto a cloth and start polishing. Polishing and protective properties.



colourless

Class :
A1, A7 (on going)



4586A4 650 ml aerosol

2586J1 5 l jerrycan

2586U2 200 l drum



GREASES

CT 6092

6092

TRANSPARENT DIRECT CONTACT GREASE

Very high-quality translucent grease for the food and food processing industry for applications where direct contact with food is required or is unavoidable. 3H certified: This grease can be used on grills, bread pans, knives, boning benches, cutting boards and other hard surfaces...



Colourless
T° : -15 to +180°C
Grade : 2
Class : 3H

36092C4 400 g cartridge

36092B7 1 kg tin

VASCO

657

VASELINE CODEX GREASE

Specifically designed for the lubrication of delicate mechanisms: Textile, food, pharmaceutical, watch making industry etc.

■ White
T° : -20 to +50°C
Grade NLGI : 4/5
Water resistance:
good
Class : H1 (on going)



3657C3 310 ml cartridge

3657B7 1 kg tin

3657S1 5 kg tub

6658T3 100 g tube (VASCO 15)

CTSI

809

AEROSOL GREASE

High viscosity lubricant for maximum resistance to bad weather. For the semi-greasy lubrication of chains, conveyors, plastic materials, rubber, locks, hinges, open mechanisms, pharmaceutical industry equipment, ski lift poles, etc. Excellent mould releaser.



Colourless
T° : 60 to +200°C
Class : H1 (on going)



4809A4 650 ml aerosol

CT 830

616

HIGH-PERFORMANCE GREASE

Synthetic fluorinated grease, resistant to hydrocarbons and chlorates. Remains very stable over time. Recommended for difficult greasing jobs: refineries, chemical plants etc. Suitable for the lubrication of conveyors in epoxy painting booths.

■ White
T° : -40 to +280°C
4-ball EP:
800 kg
Class : H1



3616T3 100 g tube

3616C5 800 g cartridge

3616B7 1 kg tin

3616S1 5 kg tub

GREASES

SI ROBINET

651

VALVES AND TAP FITTINGS, FOOD INDUSTRIES

Lubrication of household and industrial valves and tap fittings. For metal, glass and plastic valves. Compatible with all seals and elastomers. The grease remains very stable when exposed to heat, hot or cold water or solvents. Chemically inert.

colourless
T° : -40 to +200°C
Drop point:
sans
Water resistance:
very good
Grade NLGI : 2
Class : H1



3651T3 100 g tube
3651B7 1 kg tin

NANOLUBRICANT®

2035

HIGH-TECH WHITE GREASE

tremendous potential for advanced lubrication. Multi-purpose, high-performance grease. WATERPROOF MARINE GREASE
Grease specifically developed for applications in the food industry or where clean grease is required. Resulting from ORAPI's NANOLUBRICANT® technology, this grease has outstanding anti-wear, extreme pressure and long-life properties, 2 to 4 times greater than other greases on the market.

white
T° : -30 to +150°C
Grade NLGI : 2
4-ball EP:
500 kg
Class : H1



32035C4S 400 g standard cartridge

CT 609

609

TRANSLUCENT GREASE

Does not stain, excellent water resistance. For chains, hinges, runners, cutting knives on packaging lines, sliding surfaces.

Transparent
T° : -30 to +150°C
Drop point:
none
Class : H1



4609A8 270 ml TDS aerosol
4609A4 650 ml aerosol
3609T4 200 g tube
3609C4 400 g cartridge
3609CL 400 g Lube Shuttle cartridge
3609B7 1 kg tin
3609S1 5 kg tub
3609O4 50 kg drum

CT 622

622

VERY SOFT PTFE GREASE

Lubrication under heavy loads with PTFE's lubricating effect, noise reduction. Chemical inertness. Excellent water resistance, very adhesive. Bearings, conveyors... Ideal on plastics.

white
T° : -15 to +180°C
Grade : 00
Class : H1

3622B7 1 kg tin
3622O4 50 kg drum

CT 6221

6221

SOFT PTFE GREASE

Lubrication under heavy loads with PTFE's lubricating effect, noise reduction. Chemical inertness. Excellent water resistance, very adhesive. Bearings, conveyors... Ideal on plastics.

white
T° : -15 to +130°C
Grade : 1
Class : H1



36221C4 400 g cartridge
36221B7 1 kg tin
36221O4 50 kg drum

SITEF 2

620

PTFE SILICONE GREASE

High-performance grease recommended for lubrication under vacuum in the presence of acidic or alkaline products. Excellent water resistance. Plastic-to-plastic lubrication. Does not stain. For (low speed) ball bearings operating at very high or very low temperatures, tap fittings, valves etc. in the refrigeration, chemical, petroleum and aeronautical industries, industrial bakeries, etc.

white
T° : -60 to +280°C
Grade NLGI : 2
Class : H1



3620T4 200 g tube
3620C4 400 g cartridge
3620B7 1 kg tin

CT FLON AL

618

PTFE GREASE

Greasing under heavy loads with the lubricating effect of PTFE, noise reduction. Chemically inert. Excellent water resistance, good adhesive properties. Bearings, conveyors, etc. ideal for use on plastics.

white
T° : -40 to +170°C
DN Factor:
350 000
Class : H1



4618A4 600 ml aerosol
3618C4 400 g cartridge
3618B7 1 kg tin
3618S1 5 kg tub

CT 615

615

WHITE GREASE

Food-related industries. Water and detergent resistant. Direct and centralised greasing. Bearings, cams, packaging machines, conveyors etc.

white
T° : -20 to +160°C
Grade NLGI : 1,5
Class : H1



3615T3 100 g tube
3615C4 400 g cartridge
3615CL 400 g Lube Shuttle cartridge
3615B7 1 kg tin
3615S1 5 kg tub
3615O1 20 kg drum
3615O4 50 kg drum

EVANESCENT OILS

FTS 21

872

MEDIUM AND THIN MATERIAL CUTTING AND STAMPING

Chlorine-free, sulphur-free thermodegradable fluid for delicate working operations on thin materials designed for the food and pharmaceutical industry. Leaves a light residual film, nearly imperceptible Thermodegradable.

colourless
Viscosity at 25°C:
1,45 cSt
Class : H1



287201 20 l drum

2872U2 200 l drum



ANTI-SEIZE PASTES

NANOLUBRICANT®

2030

WHITE, HIGH TECHNOLOGY

Anti-seize paste specifically developed for applications in the food industry or when a clean paste is required. Resulting from ORAPI's NANOLUBRICANT® technology, this paste has outstanding anti-wear and anti-seize properties, 3 to 10 times greater than standard market pastes.

white
T° : -40 to +150°C
Grade NLGI : 1
Class : H1



32030B7 1 kg box

32030S1 5 kg tub

NANOLUBRICANT®

2040

WHITE, WATERPROOF

Clean mounting, assembly and surface treatment paste. Protects against corrosion, seizing and wear caused by micro-movements and inclement weather. Withstands high temperatures and facilitates dismantling. Good adhesive properties, does not run.

white
T° : -60 to +200°C
4-ball EP: 800 kg
Wear: <0,4 mm
Class : H1



42040A4 650 ml aerosol

BA

640

FOOD INDUSTRY

White and clean assembly and mounting paste. Contains very high technology lubricating powders. Does not stain. Product especially formulated for maintenance workshops. To treat tooling, tools, pieces working at high temperatures: plastic moulds, in food industry, in paper mills...

white
T° : -25 à
+1000°C
Class : H1



3640T4 200 g tube

3640B7 1 kg tin

364002 25 kg drum



DRY LUBRICATION

TEFLISS 2

701

PTFE

Clean and dry PTFE-based lubricant. With a very low friction coefficient. Water repellent, does not stain. For all mechanisms requiring a thin layer of micronised PTFE: sliding panels, saw blades, runners, conveyor belts, rotary and sliding joints, copying machines, reels etc.

white
T° : -120 to
+250°C
Class : H1 (on
going)



4701A4 650 ml aerosol

POUDRE PTFE

645

PTFE POWDER

Dry lubricant based on purified and micronised PTFE. Excellent lubricant properties. Highly inert towards chemicals, compatible with rubbers. Sliding agent for assemblies (joints, fasteners, valves). Dry lubrication in case of extreme conditions. Additive for lubricants.

creamy white
T° : -120 to
+250°C
Grading:
1 à 7 µm
Class : H2

3645B7 1 kg tin

OILS

LUBRICATE

HUILE L 305

655

FOOD GRADE SYNTHETIC LUBRICANT

Multipurpose lubricant with a much higher anti-wear power than traditional lubricants. Cleans, penetrates and lubricates very quickly. Protects against corrosion. Oil designed for abattoirs, canning, biscuit and cheese plants etc. for all types of lubrication: chains, gears, pinions, slideways. The viscosity is suitable for a broad range of applications and mechanisms.

colourless
T° : -35 to +135°C
Viscosity at 40°C :
105 cSt
Class : K1 H1/H1



4565A4 650 ml aerosol TDS
2565J1 5 l jerrycan

SILAL

812

FOOD GRADE SILICONE LUBRICANT

Mould releaser for materials used in the food and pharmaceutical industries. Water repellent lubricant for chains, conveyors, open mechanisms where incidental contact with food may occur. Pharmaceutical industry, nappy folding and packaging etc. (ACS compliant).

colourless
Odor : Odorless
T° : -40 to +180°C
Class : H1



4812A4 650 ml aerosol

ORAFLO AL

707

FOOD GRADE PTFE LUBRICANT

High-tech PTFE-based lubricant. Gives all treated mechanisms long term lubrication. Does not stain. Improves friction coefficient and eliminates noises. For the food industry (abattoirs, bottle conveyors etc.)

white
T° : -20 to +230°C
Viscosity at 25°C :
44 cSt
Class : H1



4707A8 270 ml aerosol TDS
4707A4 650 ml aerosol
2707i2 1 l container
2707J1 5 l jerrycan

FLUIDE 830

830

SYNTHETIC LUBRICANT

High-tech fluid lubricant resistant to aggressive chemicals: strong oxidising agents, steam, oxygen, helium, hydrocarbons, and high temperatures. Compatible with plastic materials. Silicone-free. Can be used as a mould-release agent. To be applied in a very thin coat.

colourless
viscous liquid
Odour : none
T° : -40 to +280°C
Density : 1,9
Viscosity at 40°C :
89 cSt
Class : H1



4830A2 405 ml aerosol
3830i2 1 kg container
3830J1 5 kg jerrycan

FINE 121

810

LIGHT OIL

Highly fluid, clean lubricant for greasing delicate mechanisms. For lubricating micro-mechanisms, control apparatus, pneumatic circuits and chains in the food industry. Recommended by SEDIS. INS 3H for direct contact with foodstuffs.

colourless
T° : -30 to +150°C
Class : H1/H3,3H



2810R1 125 ml oil can
4810A4 650 ml aerosol TDS
2810i2 1 l container
2810J1 5 l jerrycan
28140U2 200 l drum

DESUCR'OIL

819

SUGAR DISSOLVING OIL

Highly penetrating, sugar dissolving and lubricating white fluid. Dissolves sugar residue, infiltrates, lubricates and protects. De-seizes mechanisms blocked by large sugar deposits. White, tasteless and odourless lubricant. Food industries (chains, pinions etc.), sweet food packaging, production and processing equipment. Water-based.

white
Transparent liquid
T° : +5 to +70°C
Flash point:
none
VOC content: 0 %
Class : H1



2819J1 5 kg jerrycan
281901 20 kg container
2819U2 200 kg drum

SILICONE V 300

825

FLUID SILICONE OIL

Highly hydrophobic silicone lubricant, to be used neat. Can be used within a broad range of temperatures with no risk of congealing; chemically inert; resists frequent washing for several months. Lubrication of all mechanisms. Pharmaceutical grade, cosmetics.

colourless
T° : -52 to +200°C
Viscosity at 40°C :
300 cSt
Viscosity at 25°C :
350 cSt
Class : H1



2825i2 1 kg container
2825J1 5 kg jerrycan



HYDRAULIC & GEAR OILS

Name	N°	Visco 40°C cSt	Visco 100°C cSt	Pour Point °C	Packaging	Categorie NSF	N°NSF
HYDRAULIC OILS JACKS AND CHAINS - COLOURLESS ODOURLESS TASTELESS							
ORALUB 32F	8942	32	7	-10	20 l	H1	155329
ORALUB 46F	8932	46	9	-10	20 l	H1	155330
ORALUB 68F	8952	68	10	-10	20 l	H1	155331
ORALUB 100F	8962	100	15	nc	20 l	H1	158115

OILS FOR GEARS AND GEAR REDUCERS – COLOURLESS ODOURLESS TASTELESS							
CB ENG AL 150	6122	150	20	-18	20 l	H1	158040
CB ENG AL 220	6123	220	24	-22	20 l	H1	156336
CB ENG AL 320	6124	320	40	-25	20 l	H1	156522
CB ENG AL 460	6125	460	55	-25	20 l	H1	155332
CB ENG AL 680	6126	680	65	-25	20 l	H1	155086

SEVERE-COLD OILS							
ICE AL 46	8933	46	8,5	-50	20 l	H1	155136



ORAPI

CLEAN & PROTECT TOGETHER

CALFLUID HEAT TRANSFER FLUIDS *CALFLUID®*

Colour	Name	N°	Visco 20°C	Visco 0°C mPa.s	Crystallization temperature	Packaging	Categorie NSF	N°NSF
CALFLUID								
Colourless	Calfluid I CONC	3200	19	105	- 50°C	20, 210, 1000, 24000 kg	HT1	158195
Colourless	V Calfluid I Vegetal	4200	19	105	< - 50°C	20, 210, 1000, 24000 kg	HT1	163974
Red	Calfluid R CONC	3000	19	105	< - 50°C	20, 210, 1000, 24000 kg	HT1	164374
Red	V Calfluid R Vegetal	4000	19	105	< - 50°C	20, 210, 1000, 24000 kg	HT1	On going

BIOLOGICAL PARTS WASHER



BIOLOGICAL PERFORMANCE

Biological parts washers clean your parts without any solvent by respecting the user's health and the environment.
The biological parts washer works with the principle of natural regeneration which use the microorganisms to simply transform pollutants into food and energy sources.
This process ensures a cost effective degreasing solution.



OPERATOR'S HEALTH

Solvent free.
Optimal hygiene and safety conditions.



SAVINGS

Consumable cost control. Microorganisms constantly regenerate the bath: no frequent bath draining.



ENVIRONNEMENT

Minimizes waste and protect the environment.

40 L PARTS WASHER

BIOLOGICAL PARTS WASHER

The parts washer keeps the bath warm at 38°C, it is equipped with several cleaning options (brush, soaking), with a stainless steel filtration system and oxygenation system.
Microorganisms constantly regenerate the bath: no frequent bath draining and you minimize the waste disposal costs.

700091XXS

Part Washer
dimension
(width x length x
height, mm)
822 x 530 x
1050

700091XXS 40 l part washer



100 L PARTS WASHER

BIOLOGICAL PARTS WASHER

The parts washer keeps the bath warm at 38°C, it is equipped with several cleaning options (brush, soaking), with a stainless steel filtration system and oxygenation system.
Microorganisms constantly regenerate the bath: no frequent bath draining and you minimize the waste disposal costs.

700091

Part Washer
dimension
905 x 650 x
1110

700091 100 l part washer



ORAPI
CLEAN & PROTECT TOGETHER

FOR MORE INFORMATION, CONTACT US:
TEL : 04 74 40 20 20 - contact@orapi.com

GLUES

FREINAGE FAIBLE/MOYEN/FORT 300/303/306**THE THREAD BRAKES EXIST IN 3 "RESISTANCES**

For assemblies that need to be disassembled in a food environment : fruit and vegetable conveyor belt, pumps for beverages, blood, dairy products..

Class : S6



1300F3	FREINAGE FORT - 50 ml bottle
1303F3	FREINAGE MOYEN - 50 ml bottle
1306F3	FREINAGE FAIBLE - 50 ml bottle

TUBELOCK EXTRA 077**SEALING OF FITTINGS AND PLUGS**

Multi-purpose, single-component anaerobic adhesive for sealing metallic threaded caps, pipes and connections. Effective on all types of metal at low and high pressure. Sealant for hot and cold water, solvents, oils, refrigeration, petrol, compressed air and gas. Heaters, toilets, air conditioning, hydraulic and pneumatic mechanisms, vehicles, etc.



■ yellow-orange
Thixotropic putty
Continuous
operating T°:
- 60 to + 150°C
Mechanical resistance
on steel M10
(NFT 76.124) :
10 to 20 N.m
Setting time
at 20°C: < 5 min
copper and copper
alloys: 2 to 10 min
on steel. < 30 min
on inox
Maximum
operation gap: 0,4
mm
Class : P1

1077F7 50 ml squeeze bottle

LUBRISEAL RTV ACETIQUE 100
TRANSPARENT ADHESIVE MASTIC

Flexible bonding and sealing. Metal, glass and ceramic parts, expansion joints, wire insulation, etc. Soundproofing, insulation and mechanical applications.

Transparent
T°: -65 to +250°C
Film formation:
10 min
Complete drying:
24 h
Shore A hardness:
25-33
Class : S2



6100T3	100 g tube
1100C3	310 ml cartridge

LUBRISEAL RTV ACETIQUE 101
WHITE ADHESIVE MASTIC

Flexible bonding and sealing. Metal parts, glass, ceramic, expansion joints, wire coating etc. Insulation of electrical wires and appliances. Soundproofing, insulation and mechanical applications.

■ white
T°: -65 to +250°C
Film formation :
10 min
Complete drying:
24 h
Shore A hardness:
15-25
Class : S2



1101C3 310 ml cartridge

ORABOND BLANC 125
VERY HIGH PERFORMANCE PRODUCT

Bonds, assembles and seals everything. New generation elastic putty sealant. Excellent adhesion to stainless steel, aluminium, wood, zinc, lacquer, stone, glass wool, chipboard, etc. Can be applied onto humid surfaces and surfaces completely immersed under water. Can be painted. Odourless. Does not drip. Ideal for replacing stainless steel/stainless steel welds. Very high tackiness.

■ white
T°: -40 to +150°C
Shore A hardness:
45-60
Consumption:
1 cartridge =
1,5 m² ou 15 m
Class : P1 (on
going)



1125C6 290 ml cartridge

C 2040 355
ELASTOMER

Quick-setting adhesive for bonding rubber joints, plastic, glass and O-rings.

colourless
T°: -50 to +80°C
Viscosity :
20-40 cP
Setting time:
5 to 60 s
Shearing strength:
27,5 MPa Store
in a cool place
(5-15°C)
Class : S4



1355F1	5 g bottle
1355F2	20 g bottle
1355F3	50 g bottle
1355F6	500 g bottle

ACTIVATEUR 3140 015
SPEEDS UP POLYMERISATION OF ANAEROBIC RESINS

Speed up the polymerisation of anaerobic resins, reducing setting time.
Recommended:
- for use on galvanised or painted surfaces, stainless steel and aluminium,
- for large gaps
- when the temperature is below 10°C

■ copper red
liquid
Class : P1



1015M1 100 ml pump spray



WASHING TRANSPORT

PLATINIUM

SUPER ACTIVE SHAMPOO

Super concentrated shampoo that easily removes traffic film and the various soils encountered on the bodies (insects, grease ...) without affecting paints and varnishes or application equipment. Facilitates the removal of all grease, dirt ... and has an active dense foam increasing the contact time and therefore detergency. Given its special formulation, it is as effective on the body as well as it is on the tarpaulin for truck trailers, public works, transport... and has an easy rinse.

TN05050

Temperature of use :
40°C
Dosage **2 to 5 %**
(manual use)
0,5 to 1 %
(roll-over vehicle wash system)
contact time :
3 to 5 mn
Class : **C1**




TN050500441 5 kg jerrycan
TN050500447 25 kg drum
TN050500450 220 kg drum
TN050500483 1050 kg container



BACTIMOSS

FOAMING DISINFECTANT

Foaming bactericide and fungicide disinfecting detergent. For the interior of refrigerated lorries and food cisterns. Removes tannins and traces of blood. Removes heavy soil from painted floors.

TN02089

Service temperature :
35°C
Dosage : **4 to 6 %**
(LP spraying or foam gun)
Contact time :
15 to 20 mn
Class : **D1**




TN020890447 25 kg drum
TN020890450 230 kg drum
TN020890483 1150 kg container




DEBIO

TAR REMOVING

Powerful emulsifiable powders remover based on plant extracts. Cleaning and degreasing of very dirty mechanical parts, combustion residues, oil and traces of tar and removes bitumen and its derivatives. Can also be used as anti-adherent and release agent: concrete, tar and elimination of asbestos glues. Without VOC, rinse with water.

C330

Pale yellow
Flash point : **170°C**
IKB : **> 80**
Class : **K1**



C330/0005 5 kg jerrycan
C330/0030 30 l drum
C330/0210 210 l drum
C330/01000 1000 l container



ACID

CLEANING SCRUBBER

Acid scrubber. Detergent with very strong wetting power. Interior cleaning for aluminium and stainless steel cisterns. Cleans aluminium rims and varnished or painted hub caps. Also removes deep-seated dirt from boat hulls.

TN01032

Service temperature :
45°C
Dosage : **5 to +10%**
Time contact :
5 to 10 mn
Class : **A8**




TN010320441 5 kg jerrycan
TN010320446 23 kg drum
TN010320450 260 kg drum
TN010320483 1300 kg container



MECA FORTE

ULTRA-POWERFUL DEGREASER

Ultra-powerful alkaline degreasing renovator. Cleans fifth wheels, engines, chassis, tarpaulins, etc. Suitable for foam cannons. Not recommended for aluminium.

TN02638

Service temperature :
Room temperature
Dosage : **2 to 4%**
(LP spray)
Time contact :
3 to 5 mn
Class : **A8**




TN026380441 5 kg jerrycan
TN026380447 25 kg drum
TN026380450 260 kg drum



DDA

NON-FOAMING DISINFECTANT

Non-foaming bactericide and fungicide* detergent. Chlorinated product for use inside refrigerated lorries and food cisterns. Removes tannins and traces of blood.

TN02009

Service temperature :
35°C
Dosage : **0,6 to 2%**
(LP spraying)
4 à 6 % (foam gun)
Time contact :
15 to 20 mn
Class : **D1**




TN020090447 25 kg drum
TN020090450 240 kg drum
TN020090483 1200 kg container



AFX

FOAMING FOOD DEGREASER

Degreaser for cleaning vegetable or animal fat residues. Also effective for stripping unpolymerized glues ... Very wetting, it is particularly suitable for tank interiors, tanks ...

TN02682

Service temperature :
<40°C
Dosage :
1 % (aspersion)
5 % (foam gun)
Time contact :
5 to 20 mn
Class : **C1**




TN026820446 21 kg drum
TN026820450 240 kg drum
TN026820483 1000 kg container



MYCONET

SURFACE DISINFECTANT

Bactericide, fungicide and virucide surface disinfectant. Slightly foaming and wets easily. For disinfecting the interiors of warehouses, refrigerated lorries and food cisterns.

TN03091

Service temperature :
ambiante
Dosage : **1 to 2,5%**
(BP spraying or foam gun)
Time contact :
5 mn
Class : **D1**




TN030910447 22 kg drum



WASHING TRANSPORT

OXYD

TN05090

DEOXIDIZING CLEANSER

Acid-based scrubbing cleaner that removes oxidation. Foaming descaler, effective on train/road containers, floors (refrigerated lorries). Tiled and painted floors. Formulated for aluminium: rims, rails, cisterns, etc. Suitable for galvanised steel, cement stains.

Service temperature :
40°C
Dosage : **10 to 30%**
(BP spray)
Time contact :
3 to 5 mn
Class : **A8**



TN050900441	5 kg jerrycan
TN050900446	24 kg drum
TN050900450	270 kg drum
TN050900483	1300 kg container
TN050910447	25 kg drum (PAE 25%)



MECA SUP

TN05162

FOAMING MECHANICAL DEGREASER

Highly concentrated, powerful degreaser, effective on soot, combustion residue, etc. Foaming alkaline product, can be used hot.

Service temperature :
40°C
Dosage : **5 to 30%**
(HP spray)
Time contact :
5 to 10 mn
Class : **C1**

TN051620441	5 kg jerrycan
TN051620447	25 kg drum
TN051620450	230 kg drum
TN051620483	1100 kg container



SCM

TN05169

DEGREASING SHAMPOO

Body shampoo, powerful high foaming detergent. Particularly suitable for vehicles and parts in case of important staining.

Service temperature :
<40°C
(50°C for
mechanical parts)
Dosage : **3 to 8 %**
(bodyworks)
15 to 30 %
(tarpaulins,
chassis, engines)
Time contact : **5 to 10 mn**
Class : **C1**

TN051690441	5 kg jerrycan
TN051690447	25 kg drum
TN051690450	230 kg drum
TN051690483	1100 kg container



NVA

TN05600

FOOD-GRADE SHAMPOO, LASTING SHINE

Cleaner for food vehicles such as tanks or refrigerated trucks. Provides effective washing before the disinfection step. Enriched formula that provides lasting shine.

Service temperature :
<40°C
Dosage : **3 to 6%**
Time contact :
3 à 5 mn
Class : **C1**

TN056000447	25 kg drum
TN056000450	230 kg drum
TN056000483	1100 kg container



SA

TN05604

INTERIOR AND EXTERIOR SHAMPOO

Food grade shampoo for tanks, refrigerated trucks. Interior/exterior wash that leaves a correct shine before the disinfection step.

Service temperature :
< 50°C
Dosage : **4 to 6%**
Time contact : **3 to 5 mn**
Class : **C1**



TN056040450	230 kg drum
-------------	-------------



NVA +

TN051U0

CONCENTRATED FOOD-GRADE SHAMPOO

Concentrated anti-static shampoo. Interior and exterior washing of vehicles used to transport foodstuffs. Dye and fragrance free. Leaves a high shine after application. Suitable for wash heads (CIP).

Service temperature :
45°C
Dosage : **3 to 5%**
(BP spray)
0,5 to 1 %
(roll-over brushes)
Time contact :
3 to 15 mn
Class : **C1**

TN051U00447	25 kg drum
TN051U00450	220 kg drum
TN051U00483	1085 kg container



SA +

TN051V0

REINFORCED SHAMPOO

Food shampoo for indoor and outdoor cleaning of fridges, cisterns ...
Brilliance enhanced after application.

Service temperature :
<40°C
Dosage : **2 to 5%**
Time contact : **5 to 10 mn**
Class : **C1**



TN051V00441	5 kg jerrycan
TN051V00450	220 kg drum



LC

TN05300

STANDARD FOOD SHAMPOO

Alkaline detergent for all surfaces: bodies, tarpaulins, side panels, bins ...
Foaming, has no phosphates or solvents, perfectly suited for the food industry.
Allows you to remove road film, grease...

Service temperature :
<40°C
Dosage : **5 to 10%**
Time contact :
3 to 5 mn
Class : **C1**

TN053M00447	23 kg drum
TN053M00450	210 kg drum
TN053M00483	1000 kg container





ORAPI FOOD RANGE - LABEL NSF

Find all the certifications on www.nsfwhitebook.org. Version 04/2022

86 products with certificates

Present in **13 categories !**
N°1 in the world!

























NEW !

BLUE CAPS ON
AEROSOLS : MORE
FOOD SECURITY



Reference	Designation	Application	% free MOH	Categories NSF	Numbers NSF
PENETRATE & RELEASE					
799	REDUCE AL (vrac/aéro)	Degrippant		H1/H1 H2	144487/ 153017
817	DEGRYP'BIO (aéro)	Degrippant bio		H1	162813
CLEAN - SOLVENTS					
568	ORASOLV A	Solvent dry	96 %	K1	140157
513	ORASOLV N	Solvent fountain pe=60°C	0 %	K6	164696
513V	ORASOLV VEG 3 AL	100% vegetable based solvent		K1	163819
544	ORASOLV T	Solvent pe=40°C		A7, K1	140137
576	ORASOLV R2	Solvent free VOC		H1/K1	154828/154828
582	NATUR'SOLV	Solvant vegetable		K1, K2	154534
543	ORASOLV S1	Solvent for inks		K1, K3	154677
5164	DECOLETIK	Label puller		K3	164631
CLEAN - DETERGENTS					
C027	DELICAL	Food équipement descaler		A3, C1	158782
535	ORARENOV	Acid descaler		A8, C1	154676
530	ORANET A	Alkaline detergent		A1,A8	136320
536	ORANET F	Degreasing cleaner		A1	154818
9062	MECAMATIC	Alkaline detergent		A1	153582
5002	NET MOUSS	Aerosol cleaning foam	94 %	A1	152783
5152	OURAGAN	Polyvalent detergent		D1	156657
533	ORANET S+	Non-foaming cleaner		C1	158204
586	BRILLINOX	Stainless steel cleaner		A1, A7 (on going)	INS K1
GREASES					
609	CT 609	Transparent grease		H1	136318
618	CT FLON AL	Teflon grease		H1	140136
6092	CT 6092	Transparent contact grease		3H	155343
615	CT 615	White grease		H1	153188
616	CT 830	Acid-resistant grease		H1	153011
620	SITEF 2	Teflon silicone paste		H1	153016
622	CT 622	PTFE grease grade 00		H1	162912
6221	CT 6221	PTFE grease grade 1		H1	162913
2035	NANOLUBRICANT 2035	High technology grease		H1	154862
657	VASCO	Vaseline grease		H1 (on going)	INS H1
658	VASCO 15	Halogen-free Vaseline		H1 (on going)	INS H1
651	SI ROBINET	Silicone paste		H1	140484
809	CTSI	Silicone grease		H1 (on going)	
GLUES					
100	LUBRISEAL RTV	Transparent silicone		S2	163170
101	LUBRISEAL RTV	White silicone		S2	163169
015	ACTIVATEUR 3140	Activator 077 and 298	99 %	P1	164446
125	ORABOND BLANC	Flexible glue		P1 (on going)	INS P1
077	TUBELOCK EXTRA	Metallic threaded Sealing		P1	146832
355	C 2040	Instant glue		S4	140139
300	FREINAGE FORT	Net brake - strong resistance		S6	164828
303	FREINAGE MOYEN	Net brake - medium resistance		S6	164829
306	FREINAGE FAIBLE	Net brake - moderate resistance		S6	164830

ANTI-SEIZE PASTE					
2030	NANOLUBRICANT 2030	High-tech anti-seize paste		H1	153010
2040	NANOLUBRICANT 2040	Waterproof anti-seize paste		H1 (in progress)	INS H1
640	BA	Anti-seize paste	55 %	H1	163898
DRY LUBRICATES					
645	POUDRE PTFE	Lubricating powder		H2	154675
701	TEFLISS 2	Lubricating dry		H1 (on going)	INS H1
OILS					
810	FINE 121 (vrac/aérosol)	Fine oil		H1/H1, 3H	141917/156477
812	SILAL	Silicone release agent 		H1	136319
819	DESUCR'OIL	Sugar dissolving oil	98 %	H1	163957
840	G 840	Glycerin oil		H1	163956
872	FTS 21	Evanescent oil		H1	141478
565	HUILE L 305 (vrac/aérosol)	Chain oil	 / 59,5 %	K1 H1/H1	140138/153070
707	ORAFILON AL (vrac/aéro)	Teflon oil	 / 34 %	H1	159477/141916
825	SILICONE V300	Silicone oil		H1	155138
746	SILICONE V7500	Viscous lubricant and release agent		H1	164392
830	HP LUB 830 (aérosol)	Fluorinated lubricant		H1	153071
HYDRAULIC AND REDUCER OILS					
8933	ICE AL 46	Big cold oil -50°C		H1	155136
6122	CB ENG AL 150	Gear oils		H1	158040
6123	CB ENG AL 220	Gear oils		H1	156336
6124	CB ENG AL 320	Gear oils		H1	156522
6125	CB ENG AL 460	Gear oils		H1	155332
6126	CB ENG AL 680	Gear oils		H1	155086
8932	ORALUB 46 F	Hydraulic oil		H1	155330
8942	ORALUB 32 F	Hydraulic oil		H1	155329
8952	ORALUB 68 F	Hydraulic oil		H1	155331
8962	ORALUB 100 F	Hydraulic oil		H1	158115
TRUCK WASH TRANSPORT					
C330	DEBIO	Degoudronnant – Debituminant	98 %	K1	163818
01032	TRANSNET ACID	Stainless steel and aluminum cleaner		A8	158192
02009	TRANSNET DDA	Non-foaming disinfectant detergent		D1	154535
02089	TRANSNET BACTIMOUS	foaming disinfectant detergent		D1	154536
02638	TRANSNET MECA FORTE	Strong alkaline detergent		A8	158203
02682	TRANSNET AFX	Tank interior degreaser		C1	154537
03091	TRANSNET MYCONET	Surface disinfectant detergent		D1	158253
05050	TRANSNET PLATINIUM	Premium shampoo		C1	156647
05090	TRANSNET OXYD	Deoxidizer		A8	154539
05162	TRANSNET MECA SUP	Foaming degreaser	95 %	C1	154868
05169	TRANSNET SCM	Powerful car body shampoo	95 %	C1	154867
05600	TRANSNET NVA	Car body shampoo		C1	154865
05604	TRANSNET SA	Car body shampoo		C1	154866
051U0	TRANSNET NVA +	Powerful car body shampoo		C1	154864
051V0	TRANSNET SA +	Powerful car body shampoo		C1	154863
053M0	TRANSNET LC	Car body shampoo		C1	154538
CALFLUID HEAT TRANSFER FLUIDS					
3200	CALFLUID I CONC	Concentrated heat transfer fluid		HT1	158195
3000	CALFLUID R CONC	Concentrated heat transfer fluid		HT1	164374
4000	V CALFLUID R CONC	Concentrated heat transfer fluid (vegetable)	49 %	HT1	164776



ORAPI

CLEAN & PROTECT TOGETHER

FIND US ON :

WWW.ORAPI.COM



ORAPI
CLEAN & PROTECT TOGETHER

225, allée des Cèdres
01150 St Vulbas – France
Tel : +33 4 74 40 20 20