

PowerTank Simplicity

The Simplicity range is designed as an entry level Powertank offering.

Our Simplicity Range is only available as a fixed speed option. The Simplicity range includes; 200ltr & 350ltr Slimline, 500ltr Utility, 200ltr, 270ltr, 340ltr, and 450ltr Coffin tanks.

It is electronically controlled, starting and stopping the pump automatically when pressure drops below 1.5 Bar

Unlike the standard Fixed Speed Powertank the Simplicity range controller does not include an integrated 3ltr pressure vessel for reducing the number of pump start & stops and does not have an adjustable start pressure feature.

Key Features

- Non-corrosive holding tank (WRAS approved material)
- Pre-fitted WRAS approved fill valve
- Minimal installation requirement
- Built-in electronic start/stop
- Dry-run protection with auto restart (time delay)
- AF Air gap
- Suitable up to Fluid Category 4

Range Options

Model
200ltr Slimline Simplicity Fixed Speed
350ltr Slimline Simplicity Fixed Speed
500ltr Utility Simplicity Fixed Speed
200ltr Coffin Simplicity Fixed Speed
270ltr Coffin Simplicity Fixed Speed
340ltr Coffin Simplicity Fixed Speed
450ltr Coffin Simplicity Fixed Speed

System Connections

Connection	Size
Inlet	½" BSP
Outlet	1" BSP
Overflow	1 ¼" BSP
Drain Off	1" BSP

	Fixed Speed Option
Power supply	240 volt, 50Hz
Controller	Presflo
Current Input	3.4 amp
Mains Power Cable	2 mtr x 1mm ² 3 core fitted with 13 amp fuse mains plug
Tank Weight Full	1ltr = 1 kg plus weight of empty tank

Pump Option	Power		Pressure	1 Bar	2 Bar	3 Bar	4 Bar	5 Bar	6 Bar
	kW	HP							
Fixed Speed	0.55	0.75	Q l/min	73	57	40	10	-	-



Fixed Speed Only