

# Technical Specification

Model:	TUFFA 1400VBFP FIRE PROTECTED TANK
Capacity (l):	1200
Diameter (mm):	1585
Height (mm):	1750
Weight (kg):	30min - 140   60min - 171
Material:	Lower Linear Density Polyethylene
Bunded:	YES

**NEED MORE  
INFORMATION?  
CALL US ON  
01889 567700**

**tuffa**<sup>®</sup>

DESIGN FUNCTION PERFORMANCE

**GUARANTEE  
10  
YEAR  
GUARANTEE**



## Specification

- Bunded construction
- Fire protection
- 2" BSP fill connection with cap & chain
- Vent
- Manual float level gauge
- Watchman sonic gauge
- 1" bottom outlet (top outlet available on request)
- Overfill prevention valve
- Tank pack (1" - 1/2" adaptor, ball valve & filter)
- Lockable flip lid

## Options & Benefits

- Independently tested to BS476: Part 22: 1987
- Independently tested to BS476 (Warrington Fire Research Centre)
- Meets Section J 5.4 of Building Regulations, Table 5.1 for Fire Protection for Oil Storage Tanks
- Simple JHA1 building control sign off

**30 and 60 minute fire protection available**



**tuffa**<sup>®</sup>  
DESIGN FUNCTION PERFORMANCE

**Contact your friendly sales team for  
information on local installers**

**Tuffa UK Limited** / Dovefields Industrial Estate, Derby Road, Uttoxeter, Staffs, ST14 8SW  
**01889 567700** / [sales@tuffa.co.uk](mailto:sales@tuffa.co.uk) / [www.tuffa.co.uk](http://www.tuffa.co.uk)

