
Swipex

Revision: 21/03/2015

Page 1 from 1

Technical data

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Swipex is a cleaning wipe of extra big size.

Properties

- Fast and permanent removal of fresh, non cured remains of adhesive and sealants.
- Cleans uncured sealant from tools and material.
- Safe in use.

Applications

- Dissolves fresh und uncured adhesion and sealant remains (Silicone, MS Polymer, PU, Acryl...) as well as PU-foam , paint etc.
- Cleaning of dirty working tables and surfaces.

Packaging

Packaging: Plastic tub containing 100 wipes.

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C. After opening close properly and consume quickly.

Substrates

On smoothed surfaces. Always apply a preliminary compatibility test on critical subfloors. Not on porous subfloors like untreated wood. Swipex can not be used to prepare surfaces before applying sealants and adhesives.

Application method

Take a wipe out of the packaging and re-seal immediately. Wipe over the stain until it disappeared and use a dry cloth to polish the surface.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label and material safety data sheet for more information.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. She is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.